ATENT COOPERATION TREATY

From the INTERNATIONAL BUREAU

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

To:

Assistant Commissioner for Patents United States Patent and Trademark Office Box PCT Washington, D.C.20231 ETATS-UNIS D'AMERIQUE

Date of mailing (day/month/year)
27 June 2000 (27.06.00)

International application No.
PCT/US99/23358

International filing date (day/month/year)
O7 October 1999 (07.10.99)

In its capacity as elected Office

Applicant's or agent's file reference
GIC-561 PCT

Priority date (day/month/year)
12 November 1998 (12.11.98)

Applicant
PETERKA, Petr et al

1.	The designated Office is hereby notified of its election made:								
	X in the demand filed with the International Preliminary Examining Authority on:								
	13 April 2000 (13.04.00)								
	in a notice effecting later election filed with the International Bureau on:								
2.	The election X was								
	was not								
	made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).								

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland

Authorized officer

Olivia RANAIVOJAONA

Telephone No.: (41-22) 338.83.38

Facsimile No.: (41-22) 740.14.35

PATENT COOPERATION TREATY

PCT

REC'D	1 9 JAN 2001	7
WIPO	PCT	$\frac{1}{2}$

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference GIC-561 PCT	FOR FURTHER ACTION See Notification of Transmittal of Internationa Preliminary Examination Report (Form PCT IPEA/416				
International application No.	International filing date (de	temational filing date (day/month/year) Priority date (da			
PCT/US99/23358	07 OCTOBER 1999		12 NOVEMBER 1998		
International Patent Classification (IPC) of IPC(7): G06F 13/12, 15/177; H04L 12/5	or national classification and 56 and US Cl.: 710/65; 705	I IPC 5/54; 709/101; 370	/401		
Applicant GENERAL INSTRUMENT CORPORA	TION				
Examining Authority and is 2. This REPORT consists of a This report is also accomplee amended and are the	transmitted to the applic total of sheets.	sheets of the desc	ription, claims and/or drawings which have g rectifications made before this Authority.		
These annexes consist of a to	_				
3. This report contains indication		ng items:			
•					
I X Basis of the repo	11				
II Priority	-				
III Non-establishmer	nt of report with regard t	o novelty, invent	ive step or industrial applicability		
IV Lack of unity of	invention				
V X Reasoned statement citations and explain	nt under Article 35(2) with anations supporting such st	n regard to novelt atement	y, inventive step or industrial applicability;		
VI Certain documents	cited				
VII Certain defects in t	the international application	n			
VIII Certain observation	ns on the international app	lication			
Date of submission of the demand		Date of completio	n of this report		
Date of submission of the comment					
13 APRIL 2000		01 NOVEMBI	ER 2000		
Name and mailing address of the IPEA	<i>r</i> us	Authorized officer			
Commissioner of Patents and Trade	marks	THOMAS LEE CONTRACTOR			
Washington, D.C. 20231	j	Telephone No. (703) 305-9717			
Facsimile No. (703) 305-3230		Telepholic 140. (703) 303-9717			

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

PCT/US99/23358

I. Ba	asis of the r	eport			<u> </u>	
1 With	regard to the	elements of the internation	nal application:*			
1. 44100		ional application as ori				
ᆜ						
x	the descrip					, as originally filed
	pages	(bee / filliones)				filed with the demand
	pages			filed with the	letter of	_ , filed with the demand
	pages		•	filed with the	letter or	
\mathbf{x}	the claims:					
L	pages	(See Attached)				, as originally filed
	pages		, as amended (together with any		ogether with any	statement) under Article 19
	nages					_ , filed with the demand
	pages		_ , filed with	the letter of $_$		
X	the drawin	gs:				11. 611.4
	pages	(See Attached)				, as originally filed
	pages					_ , filed with the demand
	pages		, , f	iled with the l	etter of	···
(T22)	.1	11	intian:			
X	the sequen	ce listing part of the des	cription.			, as originally filed
	pages	(Dec 1 Harrison)				, filed with the demand
	pages		f	iled with the l	etter of	
	pages		, , '	ned with the i		
	· ·	ge of publication of the				amination (under Rules 55.2 and
2 11/2	or 55.3).	ony nucleotide and/or s	amino acid sea	nence disclose	in the internationa	ıl application, the international
pre	eliminary ex	imination was carried of	ut on the basis	of the sequence	e listing:	
	contained	n the international app	olication in pri	nted form.		
	filed toget	ner with the internation	nal application	in computer r	eadable form.	
一百	furnished s	ubsequently to this Au	ithority in writ	ten form.		
	furnished s	ubsequently to this Au	thority in com	puter readable	form.	
	The statem	ent that the subsequently application as filed ha	y furnished wri is been furnishe	tten sequence l ed.	isting does not go	beyond the disclosure in the
		nt that the information re			orm is identical to th	e writen sequence listing has
4 X	The amen					
لنتي	ر ا		NONE			
		•	NONE			
		:lailiis, 140s	NONE			
ج ۱			me of the amon	dments had not	been made since the	ey have been considered to go
5.	I have report	has been drawn as it (sor	dicated in the S	upplemental Bo	(Rule 70.2(c)).**	o, in to occir considered to go
in	alacament she	as which have been furnish	hed to the receiv	ine Office in resi	onse to an invitation	under Article 14 are referred to ntain amendments (Rules 70.16
**An	v renlacemei	t sheet containing such a	amendments mu	st be referred to	under item 1 and	annexed to this report.

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/US99/23358

citations and explanations supporting	such stateme	rd to novelty, inventive step or industrial applicant	
statement			YES
Novelty (N)	Claims	1-20	NO
	Claims	NONE	NO
Inventive Step (IS)	Claims	NONE	YES
mventive step (15)	Claims	1-20	NO
T. I. A. a. Landinghility (IA)	Claims	1-20	YES
Industrial Applicability (IA)	Claims	NONE	NO
shows a television set-top terminal [col 3, lin	r PCT Article 3 les 15-20], com ng computer program code m	33(3) as being obvious over Sreenan, USPAT 5,742,772. prising: ogram code means [col 11, line 54]; and eans to implement an Application Programming Interface [col 11, lines 43-44] at the terminal, wherein:	

economical fashion [col. 1, lines 23-26]. Sreenan particularly provides a method for implementing resource managment via API. col. 3, lines 53-54, col. 4, lines 42-44. Sreenan also teaches that terminals, including set-top boxes, are equipped with resources, i.e., broadband network access, I/O devices, such as a graphical user interface (GUI), display, speaker, microphone and/or camera [col. 3, lines 15-20]. Thus, at the time the invention was made, it would have been readily recognized by one of ordinary skill in the art that Sreenan's API resource management may obviously be implemented in a terminal such as a set-top box because it would facilitate resource management at the terminal.

Claims 2-19 lack an inventive step under PCT Article 33(3) as being obvious over Sreenan, USPAT 5,742,772. Sreenan teaches the bridge keeps track of usage of resources [col 12, lines 4-7]. It would have been manifestly obvious to those skill

Sreenan teaches a scalable technique for managing potentially complex interactions and the use of resources in an efficient and

teaches the bridge keeps track of usage of resources [col 12, lines 4-7]. It would have been manifestly obvious to those skill in the art to realize the resources can be any of well known resources [col 12, lines 21-24] such as a tuner, a modem, a database, a plug-in module, a cable, a software module, a network interface card, and a conditional access module, and to implement any well known standard to Sreenan's system such as ITU-T X.731 standard for state management. (Continued on Supplemental Sheet.)

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/US99/23358

Supplemental Box

(To be used when the space in any of the preceding boxes is not sufficient)

Continuation of: Boxes I - VIII

Sheet 10

I. BASIS OF REPORT:

This report has been drawn on the basis of the description, page(s) 1-32, as originally filed.
page(s) NONE, filed with the demand.
and additional amendments:
NONE

This report has been drawn on the basis of the claims, page(s) 33-36, as originally filed. page(s) NONE, as amended under Article 19. page(s) NONE, filed with the demand. and additional amendments:

Pages 35-36, filed with the letter of 22 September 2000.

This report has been drawn on the basis of the drawings, page(s) 1-7, as originally filed.
page(s) NONE, filed with the demand.
and additional amendments:
NONE

----- NEW CITATIONS -----

This report has been drawn on the basis of the sequence listing part of the description: page(s) NONE, as originally filed.
pages(s) NONE, filed with the demand.
and additional amendments:
NONE

V. 2. REASONED STATEMENTS - CITATIONS AND EXPLANATIONS (Continued):

US 5,742,772 A (SREENAN ET AL.) 21 APRIL 1998, see entire documentation, especially col. 11, lines 42-63. US 5,815,678 A (HOFFMAN ET AL.) 29 SEPTEMBER 1998, see entire documentation, especially fig. 1. US 5,717,691 A (DIGHE ET AL.) 10 FEBRUARY 1998, see entire documentation, especially col. 5, lines 21-39.

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:

(11) International Publication Number:

WO 00/30346

H04N 5/00, G06F 9/46

A1

(43) International Publication Date:

25 May 2000 (25.05.00)

(21) International Application Number:

PCT/US99/23358

(22) International Filing Date:

7 October 1999 (07.10.99)

(30) Priority Data:

60/107,962

12 November 1998 (12.11.98) US

(71) Applicant (for all designated States except US): GENERAL IN-STRUMENT CORPORATION [US/US]; 101 Tournament Drive, Horsham, PA 19044 (US).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): PETERKA, Petr [US/US]; 5126 Caminito Vista Lujo, San Diego, CA 92130 (US). MEANDZIJA, Branislav, N. [US/US]; 827 Coast Boulevard South, La Jolla, CA 92037 (US). MANGALORE, Geetha [IN/US]; 11674 Spring Side Road, San Diego, CA 92128 (US). ZAISER, Kurt [US/US]; 9260 Clover Glen Court, San Diego, CA 92126 (US).
- (74) Agent: LIPSITZ, Barry, R.; Building No. 8, 755 Main Street, Monroe, CT 06468 (US).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published

With international search report.

(54) Title: APPLICATION PROGRAMMING INTERFACE (API) FOR ACCESSING AND MANAGING RESOURCES IN A DIGITAL TELEVISION RECEIVER

(57) Abstract

programming An application interface (API) for managing resources in a Digital Television (DTV) Receiver/Terminal. The API provides a uniform mechanism for gaining/controlling access to resources, managing multiple resources of the same type, and accessing the individual resource's management state and status. The resources may include, for example, a tuner, a modem, a database, a plug-in module, a cable, a software module, a network interface card, or a conditional The resources are access module. monitored and controlled either locally at the terminal, or remotely, e.g., from a head-end or an uplink. The API provides a resource package (40) for registering the available resources at the terminal, a resource state management package (30) for managing states of the resources, and a registry package (20) for storing objects that represent the resources. Resources of the same type are managed as a group.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA.	Ukraine
BR	Brazil	IL.	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
СМ	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
cz	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		
1							
1							

APPLICATION PROGRAMMING INTERFACE (API) FOR ACCESSING AND MANAGING RESOURCES IN A DIGITAL TELEVISION RECEIVER

BACKGROUND OF THE INVENTION

5

10

15

20

25

30

This application claims the benefit of U.S. Provisional Application No. 60/107,962, filed November 12, 1998.

The present invention relates to an application programming interface (API) that provides a uniform mechanism for gaining/controlling access to resources, managing multiple resources of the same type, and accessing the individual resource's management state and status. The invention is suitable for use in managing resources in a Digital Television (DTV) Receiver/Terminal.

A set-top terminal, also referred to as an Integrated Receiver-Decoder (IRD) or a subscriber terminal, is a device that receives and decodes television signals for presentation by a television. The signals can be delivered over a satellite, through a cable plant, or by means of terrestrial broadcast, for example. Various applications have been proposed, or are currently available, via modern set tops, including video on demand (VOD), audio on demand, payper-view, interactive shopping, electronic commerce, electronic program guides, Internet browsers, mail services (e.g., text e-mail, voice mail, audio mail, and/or video mail), telephony services, stock ticker, weather data, travel information, games, gambling, banking, shopping, voting, and others. Applications may also enable Internet connectivity and possibly

2

Internet-based telephony. The set top functionality is enabled through specialized hardware and software.

The applications may be downloaded by terminals via a network, loaded locally (e.g., via a smart card), or installed at the time of manufacture, for example.

Moreover, with the increasing integration of computer networks such as the Internet, telephony networks, and broadband distribution networks, many opportunities arise for providing new types of applications.

5

10

15

20

25

30

However, in the new paradigm of broadcasting downloadable applications to television receivers, there is no deterministic way of predicting which applications will be running at what time, and possibly in parallel with other applications. Nonetheless, such applications must co-exist on the receiver and co-operate in such a manner that the end user has a positive experience while these applications compete for resources. For example, the applications should run without noticeable delays or interruptions.

Also, since there are only limited resources on the terminal, there is a need to monitor and control these resources, either locally or remotely from a head-end or an uplink. Such a monitoring and control mechanism should provide improved control of the receivers in the network, and should also have the capability to prevent or fix problems related to resources on the receiver.

It would be desirable to provide a mechanism for accessing and managing resources that addresses the

3

above issues. Preferably, the mechanism should be implementable in an API.

The API should be compatible with Java(tm), ActiveX(tm) or an equivalent type of component based object-oriented technology.

5

10

15

The API should be compatible with Digital Audio Visual Council (DAVIC), American Television Standards Committee (ATSC) T3/S17 Digital TV Application Software Environment (DASE), Digital Video Broadcast (DVB) - Multi-Media Home Platform (MHP), and other related environments.

The system should be compatible with the ITU-T X.731 standard for state management.

The present invention provides a system having the above and other advantages.

4

SUMMARY OF THE INVENTION

The present invention provides an application programming interface (API) for a television terminal that provides a uniform mechanism for gaining/controlling access to resources, managing multiple resources of the same type, and accessing the individual resource's management state and status.

5

10

15

20

25

The terminal may be a DTV receiver, set-top box, IRD, TV-enabled PC, or the like. An application may use a resource, which is usually a device, function or a process on the receiver (e.g., tuner, modem, database, plug-in module, cable, software module, network interface card, persistent storage, TV screen space, memory, CPU, conditional access (CA) module, etc.)

Moreover, individual resources may advertise changes in their state and status according to their capabilities and complexity. Applications which are using these resources may monitor the state and status changes and adjust their own behavior accordingly. Management applications, whose purpose is to monitor the behavior of resources to collect statistics, finetune the receiver configuration and/or detect and fix or prevent problems (e.g., resource conflicts, malfunctions, etc.) The management applications may be downloaded or otherwise provided (e.g., locally via a smart card or at the time of manufacture or installation) to all or selected receivers to perform such functions using this API.

5

The API includes three packages: resource, management and registry. The resource package depends on the registry and management packages.

The API is preferably independent of an operating system and hardware of the terminal.

5

10

15

20

25

30

In a particular implementation, a television settop terminal is provided that includes a computer readable medium having computer program code means, and means for executing the computer program code means to implement an Application Programming Interface (API) for accessing and managing multiple resources at the terminal. The API provides a resource package for registering the available resources at the terminal, a resource state management package for managing states of the resources, and a registry package for storing objects that represent the resources.

The resource objects, in this context, are software objects as known from the field of object-oriented technology. The objects represent the real resources at the terminal. A ResourceRegistry is a convenient place where an application can learn what types of resources are available, and retrieve a ResourceType Manager for a specific type of resource. Additionally, an application can determine how many, and which, resources are available, and possibly access/use one or more of the available resources.

The management package may manage the states of the resources according to the ITU-T X.731 standard for state management.

The available resources may include a tuner, a modem, a database, a plug-in module, a cable, a

6

software module, a network interface card, and a conditional access module, for example.

5

10

15

20

25

The API may provide a resource registry for maintaining a record of resource managers that provide access to individual resources.

The API may be independent of an operating system and hardware of the terminal.

The API may group resources of the same type, and manage the grouped resources as a group.

The API may monitor behavior of the resources, and attach (e.g., associate) corresponding management information to the resources.

The API may enable the resources to advertise their respective states to at least one application at the terminal. The API may also enable the application to access the advertised states of the advertising resources.

The API may enable administrative locking and unlocking of the resources.

The API may enables the resources to advertise respective alarm statuses, availability statuses, procedural statuses, operational states, administrative states, and usage states thereof to applications at the terminal.

A corresponding method is also presented.

7

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows package relationships and dependencies in accordance with the present invention.

FIG. 2 illustrates a resource package class/interface diagram in accordance with the present invention.

5

15

FIG. 3 illustrates a management package class/interface diagram in accordance with the present invention.

10 FIG. 4 illustrates a registry package class/interface diagram in accordance with the present invention.

FIG. 5 illustrates an example class/interface diagram that shows how the resource, management and registry packages may be used with a network interface (tuner) in accordance with the present invention.

8

DETAILED DESCRIPTION OF THE INVENTION

1. Introduction

5

10

15

20

25

30

The present invention relates to an application programming interface (API) that provides a uniform mechanism for gaining access to resources (ResourceRegistry), managing multiple resources of the same type (ResourceTypeManager) and accessing the individual resource's management state and status (GenericResource and ObjectState).

For example, downloadable applications (e.g., Electronic Program Guide - EPG, stock ticker, etc.) may need to access these resources.

The invention describes a Resource Management API and its relationships to other related packages, specifically the Registry package, and how it can be applied to existing resources such as the Digital Audio Video Council (DAVIC) tuning resource (NetworkInterface).

Note that portions of the disclosure were generated automatically from Rational Rose(tm) CASE tool, developed by Rational Software Corporation, USA. The figures use the Rational Rose (tm) depiction of the Unified Modeling Language (UML), which is a language for specifying, constructing, visualizing, and documenting the artifacts of a software-intensive system. A class diagram represents the static structure of a system, and shows a pattern of behaviors that the system exhibits. This is accomplished by showing the existence of classes and their relationships. Each class is represented by a box with

9

three sections. The top section lists the class name. The middle section denotes a list of attributes, and the bottom section denotes a list of operations.

A solid or dashed line between classes denotes an association or dependency. A white diamond tip denotes aggregation by reference, while a black diamond tip denotes aggregation by value. A triangular arrowhead denotes a restricted navigation, e.g., inheritance of operation but not of structure.

Moreover, interfaces and classes begin with an uppercase letter, while methods begin with a lowercase letter.

A class is a template that defines a data structure, method and function calls for an object. An interface defines a set of methods/function calls that can be manipulated by a class. The class provides the code for implementing an interface.

2. Model Description

5

10

15

20

25

FIG. 1 shows package relationships and dependencies in accordance with the present invention. The API includes three packages: resource 40, management 30 and registry 20. The resource package depends on the registry and management packages.

2.1 Resource Package

FIG. 2 illustrates a resource package class/interface diagram in accordance with the present invention. The object diagram describes the resource management API of the present invention. A ResourceRegistry 100 is the central registry of all

10

available resources. The ResourceRegistry is the single place where a downloaded application must go to learn about existing resources.

5

10

15

20

25

30

ResourceTypeManager 120. The DAVIC

NetworkInterfaceManager is an example of a

ResourceTypeManager since there may be more than one

NetworkInterface in the DTV receiver. Individual

resources implement the GenericResource interface 140,

which identifies the name and type of the specific

resource and, in turn, implements the ObjectStates

interface 130 providing access to all or an appropriate

subset of resource states and status information.

A state is accessed to learn the current value of the state.

The Event-Listener model provides a mechanism to inform listeners about changes in the ResourceRegistry 100, such as addition of new resources or their removal from the registry.

As is known, Java defines an Event-Listener pattern which allows objects to register as listeners to another object. If there are any changes with this object, it sends an event to the listening object.

A ResourceType interface 110, RegistryChangeEvent class 150, ResourceChangeCause interface 160, and ResourceRegistryEvent class 170 are also provided.

Exceptions 180 can also be defined. Specifically, the structure is set up so that security can be used to allow some applications to access resources and some other not. If this is desirable, it may be done implicitly (already built into Java), or explicitly by

11

defining new Exceptions.

5

10

15

20

25

2.2 Management Package

FIG. 3 illustrates a management package class/interface diagram in accordance with the present invention. The diagram describes those classes and interfaces related to state management, specifically managing resource states based on the ITU-T management standard. It is separated into its own package since it can be applied to any manageable object, such as DTV receiver resources, downloadable applications, etc.

The management package includes an AdministrativeState interface 205, an OperationalState interface 210, a UsageState interface 215, an AlarmStatus interface 225, an AvailabilityStatus interface 230, a ProceduralStatus interface 235, an Exception class 240, a ResourceStateException class 245, a StateChangeListener interface 250, an EventObject class 255, a SourceIndicator interface 260, and a StateChangeEvent class 265.

A specific resource is free to support a subset of the defined states and status attributes as appropriate to the specific resource functionality. DigitalTV Application Software Environment (DASE) may mandate a subset of these in order to provide for a better interoperability between applications and resources with respect to management.

2.3 Registry Package

12

FIG. 4 illustrates a registry package class/interface diagram in accordance with the present invention.

The Registry package provides a basic mechanism to construct a Registry object of any kind. The Registry is a base interface which is extended by all specific Registries, such as the ResourceRegistry 100.

5

10

15

20

25

There is a RegistryListener 345 and RegistryChangeEvent 150 associated with this package. The listener interface 345 is used by any object that wants to be notified of any changes in the Registry 310. Changes are considered those that affect the Registry itself (not necessarily the individual elements in the registry), such as adding or removing elements to/from the Registry 310. The RegistryChangeEvent 150 is an abstract class which will be extended by the specific registry events.

Since most of the API is defined in terms of Java Interfaces, the RegistryFactory 315 is a class that hides the actual object construction implementation.

A RegistryType interface 305, UserRegistry interface 320, PreferenceRegistry interface 325, ApplicationRegistry interface 330, and EventObject class 335 are also provided. The Registry object serves as a generic mechanism for registering similar types of objects in the registry. That is, users are registered in a UserRegistry, and user preferences are registered in a PreferenceRegistry, as discussed in commonly-assigned PCT Patent Application No.

, filed October 7, 1999, and entitled "Digital Television Receiver User Management"

PCT/US99/23358

Application Programming Interface (API) For Downloadable Broadcast Applications."

Applications are registered in an

ApplicationRegistry, discussed in commonly-assigned PCT

Patent Application No. ______, filed October 7,

1999, and entitled "Software Application Lifecycle And

Management For Broadcast Applications."

2.4 Tuning Package

WO 00/30346

5

10

15

20

25

30

FIG. 5 illustrates an example class/interface diagram that shows how the resource, management and registry packages may be used with a network interface (tuner) in accordance with the present invention. The diagram shows how the Resource package classes can be applied to already defined resources. Generally, the figure is an example of how the resource, management and registry packages may be used.

This example shows the DAVIC tuning API (org.davic.net.tuning) where the NetworkInterfaceManager 420, which manages multiple NetworkInterfaces 430, can be considered as the generic ResourceTypeManager 120. Classes 420 and 430 are from the DAVIC tuning package. The NetworkInterface 430, which represents the specific resource, can implement the GenericResource interface 140 and, in turn, the ObjectStates interface 130.

A ResourceServer interface 410 is also provided. A ResourceServer is another interface from the DAVIC set of packages. This example shows how the present invention can be applied to an existing resource that is defined by another organization - DAVIC, in this

14

case.

5

10

15

20

25

3. Class and Interface Specification

The following sections describe the individual classes, interfaces and their methods.

3.1 Resource Package

This package provides classes and interfaces related to resource management functions.

3.1.1 ResourceRegistry

This interface 100 defines the necessary functionality behind the ResourceRegistry as applicable to an application. It lists resources. For example, a downloadable application may ask the ResourceRegistry what types of resources are available on the terminal, and then get the ResourceTypeManager to request access to a specific resource. ResourceRegistry 100 is derived from ResourceType 110 and Registry 310.

Public Operations:

getResourceTypeManager (resourceType : short) :
ResourceTypeManager

Returns a Resource Type Manager which manages a collection of resources of the specified type. Returns Null if this type of a resource does not exist.

getResourceTypes () : short[]

This method returns a list of supported resource types.

Public operations are those methods that may be called and used by other objects since they are visible outside of the object (e.g., class). In contrast,

15

private operations are visible only to the class/interface itself.

3.1.2 ResourceTypeManager

This interface 120 has to be supported by classes representing managers of a certain type of a resource. It is expected that most ResourceServers from the org.davic.resources package will implement this interface. It is derived from ResourceType 110.

Public Operations:

5

10

15

25

getResources () : GenericResource[]

Returns a list of GenericResources managed by this ResourceTypeManager.

getAvailableCount () : int

Returns the number of available resources.

getTotalCount () : int

Returns the total number of resources managed by this ResourceTypeManager.

getType () : short

Returns the type of this resource manager.

20 3.1.3 GenericResource

This interface 140 represents a Generic Resource which defines a common interface that has to be implemented by every manageable resource.

Only an applicable subset of ObjectStates 130 will be implemented by each specific resource.

The class that represents the actual resource (such as the NetworkInterface 430) or a proxy (such as the DAVIC ResourceProxy) may implement this interface.

16

It is derived from ObjectStates 130 and ResourceType 110.

Public Operations:

getType () : short

5

15

20

25

Returns the type of this resource.

getName () : String

Returns a name of this resource.

3.1.4 ResourceType

This interface defines the different types of resources, such as a network interface card, conditional access (CA) module, modem, etc.

Public Attributes:

NETWORK_INTERFACE : String = "Network Interface"
CA_MODULE : String = "Conditional Access Module"
MODEM : java.lang.String = "Telco Modem"
SECTION FILTER : String = "MPEG Section Filter"

3.1.5 ResourceRegistryEvent

This event 170 informs the RegistryListener 345 that there was a change in the Registry 310. The Event has information about the type of a resource that changed, and the nature of the change (e.g., resource added, removed, etc.).

It may be useful in some implementations to return the ResourceTypeManager 120 of the affected resource.

It is derived from RegistryChangeEvent 150.

Public Operations:

getResourceType () : java.lang.String

Returns the type of resource that has changed in the ResourceRegistry 100.

17

3.1.6 ResourceChangeCause

This interface defines possible causes for the ResourceRegistryEvent 170.

Public Attributes:

5

10

15

20

25

RESOURCE_ADDED : short = 1
RESOURCE REMOVED : short

3.2 Management Package

This package includes classes and interfaces related to object management. It can be applied in its entirety or as a subset as relevant to the specific managed entity. It is applicable for managing state and status attributes of digital television (DTV) receiver resources as well as applications.

It is based on the ITU-T X.731 standard for State Management.

3.2.1 AdministrativeState

An interface that defines Masks for different Administrative States:

-locked: The resource is administratively prohibited from performing services for its users.

-Unlocked: The resource is administratively permitted to perform the services to users.

The unlocked state is independent of its inherent operability. That is, a resource may be locked or unlocked (the Administrative State) and enabled or disabled (the Operational State) - these are independent of each other.

18

-Shutting down: Use of resource is administratively permitted to the existing instances of users only. The manager may at any time cause the object to revert to the Unlocked state.

5 Public Attributes:

UNLOCKED : int = 0×00000001

LOCKED : int = 0×000000002

SHUTTING_DOWN : int = 0×000000004

ADMIN TYPE : short = 1

10 Public Operations:

15

getAdministrativeState () : int

Called to get the current value of the Administrative State.

setLock (administrativeState : int) : void

Called to change the value of the Administrative State.

3.2.2 OperationalState

This interface 210 defines the Operational state for Resources and Application. Note that this

Management API is a generic mechanism that allows any resource or any application to implement the ObjectStates interface to support manageability. In a specific case (e.g., FIG. 5) a NetworkInterface implements the GenericResource interface 140, which in turn implements the ObjectStates interface 130, which has all the methods necessary for a resource to be managed.

-Disabled: The resource is totally inoperable and unable to provide the service to the users.

19

-Enabled: The resource is partially operable and available for use.

Public Attributes:

DISABLED : int = 0x8

ENABLED : int = 0×10

. 5

10

15

20

25

30

OPERATIONAL_TYPE : short = 2

Public Operations:

getOperationalState () : int

Called to get the current value of the OperationalState 210.

3.2.3 AlarmStatus

This interface 225 defines all the alarm states.

When the value of this attribute is an empty set,
this implies that none of the status conditions
described below are present.

-under repair: The resource is currently being repaired. When under repair value is present, the operational state is either disabled or enabled.

-critical: One or more critical alarms indicating a fault have been detected in the resource, and have not been cleared. The operational state of the managed object can be disabled or enabled.

-major: One or more major alarms indicating a fault have been detected in the resource, and have not yet been cleared. The operational state of the managed object can be disabled or enabled.

-minor: One or more minor alarms indicating a fault have been detected in the resource, and have not yet been cleared. The operational state of the managed object can be disabled or enabled.

20

-alarm outstanding: One or more alarms have been detected in the resource. The condition may or may not be disabling. If the operational state is enabled, additional attributes, particular to the managed object class, may indicate the nature and cause of the condition and the services that are affected.

The presence of the above alarm state conditions does not suppress the generation of future fault-related notifications.

10 Public Attributes:

5

20

25

UNDER REPAIR : int = 0×000000001

CRITICAL: int = 0×000000002

MAJOR : int = 0x00000004

MINOR: int = 0×000000008

15 ALARM OUTSTANDING : int = 0×0010

ALARM TYPE : short = 8

Public Operations:

clearAlarm (alarm : int) : void

Called to clear a specific alarm. The controlling process has acted on the alarm.

getAlarmStatus () : int

Called to get the current set of values of the Alarm Status.

3.2.4 AvailabilityStatus

This interface 230 defines the Availability status of a resource.

When the value of this attribute is an empty set, this implies that none of the status conditions described below are present.

21

-in test: The resource is undergoing a test procedure. If the administrative state is locked or shutting down then normal users are precluded from using the resource and the control status attribute has the value reserved for test.

Tests that do not exclude additional users can be present in any operational or administrative state but the reserved for test condition should not be present.

5

10

15

20

25

30

-failed: The resource has an internal fault that prevents it from operating. The operational state is disabled.

-power off: The resource requires power to be applied and is not powered on.

For example, a fuse or other protection device is known to have removed power or a low voltage condition has been detected. The operational state is disabled.

-off line: The resource requires a routine operation to be performed to place it online and make it available for use. The operation may be manual or automatic, or both.

The operational state is disabled.

-off duty: The resource has been made inactive by an internal control process in accordance with a predetermined time schedule. Under normal conditions the control process can be expected to reactivate the resource at some scheduled time, and it is therefore considered to be optional. The operational state is enabled or disabled.

-dependency: The resource cannot operate because some other resource on which it depends (e.g., a

22

resource not represented by the same managed object) is unavailable.

For example, a device is not accessible because its controller is powered off.

The operational state is disabled.

5

10

15

20

25

-degraded: The service available from the resource is degraded in some respect, such as in speed or operating capacity. Failure of a test or an unacceptable performance measurement has established that some or all services are not functional or are degraded due to the presence of a defect. However, the resource remains available for service, either because some services are satisfactory or because degraded service is preferable to no service at all. Object specific attributes may be defined to represent further information indicating, for example, which services are not functional and the nature of the degradation. The operational state is enabled.

-not installed: The resource represented by the managed object is not present, or is incomplete. For example, a plug-in module is missing, a cable is disconnected or a software module is not loaded. The operational state is disabled.

-log full: This indicates a log full condition, the semantics of which are defined in CCITT Rec. X.735 | ISO/IEC 10164-6.

Public Attributes:

INTEST: int = 0×00000400

FAILED: int = 0×000000800

30 POWEROFF: int = 0×00001000

OFFLINE: int = 0×000002000

23

OFFDUTY: int = 0×000004000

DEPENDENCY: int = 0×00008000

DEGRADED: int = 0×00010000

NOT INSTALLED: int = 0×00020000

LOG FULL : int = 0×00040000

AVAILABILITY TYPE : short = 32

Public Operations:

5

10

15

20

25

30

getAvailabilityStatus () : int

Called to get the current set of values of the AvailabilityStatus 230.

3.2.5 ProceduralStatus

This interface 235 defines the Procedural status.

The procedural status attribute is supported only by those classes of managed objects that represent some procedure (e.g., a test process) which progresses through a sequence of phases. Depending upon the managed object class definition, the procedure may be required to reach certain phase for the resource to be operational and available for use (i.e., for the managed object to be enabled). Not all phases may be applicable to every class of managed object. If the value of this attribute is an empty set, the managed object is ready, for example, the initialization is complete.

When the value of this attribute is an empty set, this implies that none of the status conditions described below are present.

-initialization required: The resource requires initialization to be invoked by the manager (e.g., ResourceTypeManager 120) before it can perform its

24

normal functions, and this procedure has not been initiated. The manager may be able to invoke such initialization through an action. The terminating condition may also be present. The operational state is disabled.

-not initialized: The resource requires initialization before it can perform its normal functions, and this procedure has not been initiated. The resource initializes itself autonomously, but the operational state may be either disabled or enabled, depending upon the managed object class definition.

-initializing: The resource requires initialization before it can perform its normal functions, and this procedure has been initiated but is not yet complete. When this condition is present, the initialization required condition is absent, since initialization has already begun. The operational state may be disabled or enabled, depending upon the managed object class definition.

-reporting: The resource has completed some processing operation and is notifying the results of the operation, e.g., a test process is sending its results. The operational state is enabled.

-terminating: The resource is in a termination phase. If the resource does not reinitialize itself autonomously, the initialization required condition is also present and the operational state is disabled. Otherwise, the operational state may be either disabled or enabled, depending upon the managed object class definition.

Public Attributes:

5

10

15

20

25

30

INIT_REQUIRED : int = 0x00000020
NOT_INITIALIZED : int = 0x00000040
INITIALIZING : int = 0x00000080
REPORTING : int = 0x00000100
TERMINATING : int = 0x00000200
PROCEDURAL_TYPE : short = 16
Public Operations:

getProceduralStatus () : int

Called to get the current set of values of the Procedural Status.

3.2.6 UsageState

5

15

20

25

This interface 215 defines the Mask (i.e., the bit assignment shown below for IDLE, ACTIVE, etc.) for UsageState, which is the name of the interface which represents the concept of Usage State from the ITU-T X.731 standard.

-Idle: The resource is not currently in use.

-Active: The resource is in use, but has spare operating capacity to provide additional users at this instant.

-Busy: The resource is in use, but has no spare operating capacity to provide additional users at this instant.

Public Attributes:

IDLE : int = 0x00000020

ACTIVE : int = 0×00000040

BUSY : int = 0×000000080

USAGE TYPE : short = 4

Public Operations:

30 getUsageState () : int

Called to get the current value of the Usage State.

3.2.7 ObjectStates

This interface 130 allows objects, which are meant to be managed in a standard way, to implement a unified interface which supports all or a suitable subset of states and status values. The defined state and status attributes are specified by the ITU-T standard X.731 for State Management.

It is derived from AlarmStatus 225,
ProceduralStatus 235, AvailabilityStatus 230,
UsageState 215, OperationalState 210, and
AdministrativeState 205.

Public Operations:

getStatesSupported () : short[]

Called to determine which state and status attributes are supported by the class implementing this interface.

addStateChangeListener (listener :

20 StateChangeListener) : void

5

10

15

25

Called to register a StateChangeListener for StateChangeEvents.

removeStateChangeListener (listener :

StateChangeListener) : void

Called to deregister a StateChangeListener.

getCurrentState () : int

Called to get the current value of all supported states. Returns a bit mask representing the individual states.

27

Called to get the current value of all supported status attributes. Returns a bit mask representing the individual status attributes.

3.2.8 StateChangeListener

This interface 250 must be implemented by classes interested in being notified of state changes of objects which implement the ObjectStates interface 130. If an object which is a StateChangeListener 250 registers via the addStateChangeListener method, it will be notified by calling the stateChange method which includes the appropriate StateChangeEvent 265.

Public Operations:

5

10

15

20

25

stateChange (event : StateChangeEvent) : void

Called to notify a StateChangeListener about a

state change. The event parameter provides information
about what state has changed.

3.2.9 ResourceStateException

A base Exception class 245 related to the ObjectStates 130 interface. This exception, or its extensions, are thrown when a invalid state change would be caused by a method call. For example, an object in a Disabled state cannot perform a certain operation unless it is Unlocked. Derived from the Exception class 240.

Public Operations:

getState () : short

Called to determine which state consistency has been violated.

getValue () : int

28

Called to get the current value of the violated state.

3.2.10 StateChangeEvent

This Event 265 is fired (e.g., emitted or sent) when a state changes its value. It is distributed to all registered StateChangeListeners 250.

Derived from EventObject 255.

Public Operations:

5

getState () : short

10 Called to determine which state has changed.

getOldValue () : int

Called to determine the original value of the state.

getNewValue () : int

15 Called to determine the new value of the state.

getSourceIndicator (): short

Called to determine the cause of the event.

3.2.11 SourceIndicator

Public Attributes:

20 INTERNAL CAUSE : short = 1

State change caused by an internal activity.

EXTERNAL_CAUSE : short = 2

State change caused by an external activity.

3.3 Registry Package

This package provides a set of supporting and utility classes and interfaces used by other packages.

3.3.1 Registry

29

This interface 310 provides a common root to all specialized registry interfaces, such ApplicationRegistry 330, ResourceRegistry 100, etc. (FIG. 4). It is provided so that the RegistryFactory 315 can return a base type.

A "base type" is known from the field of objectoriented programming. To illustrate, one can define a
class with a set of functions (methods) and internal
variables (e.g., a class "Fruit" which represents fruit
and its basic characteristics). One can specialize it
by defining a new class, "Apple", which inherits
everything from the class "Fruit", and adds new
functions that are applicable only to Apples but not to
Fruit in general. "Fruit" is then referred to as a
"base class" or a "base type."

Derived from RegistryType 305.

Public Operations:

5

10

15

20

25

30

getRegistryType () : String

Called to determine the type of registry implemented by the object returned by the RegistryFactory's method getRegistry().

addRegistryListener (listener :
org.atsc.registry.RegistryListener) : void

Called to register for events generated by the Registry 310.

removeRegistryListener (listener :
org.atsc.registry.RegistryListener) : void

Called to deregister for events generated by the Registry 310.

3.3.2 RegistryFactory

30

This class 315 provides a mechanism to create objects that implement specific Registry interfaces, such as the ApplicationRegistry 330. This class is modeled after the Factory Method design pattern, which, as is known from the field of object-oriented programming, is a methodology and structure for solving a problem.

Public Operations:

RegistryFactory ():

10 Constructor:

5

15

20

25

getRegistry (registryName : String) :
org.atsc.registry.Registry

Returns an instance of an object which implements the specified registry interface. Returns null when specified registry does not exist or cannot be created. The type of the returned object will be one of the derived Registry types, such as the ApplicationRegistry 330.

As known from the field of object-oriented programming, a constructor is a method that is called for each object at the time it is created/instantiated.

3.3.3 RegistryType

This interface 305 defines names for different registry types, such as an application registry (e.g., ApplicationRegistry 330), etc.

Public Attributes:

APPLICATION_REGISTRY : String = "Application Registry"

RESOURCE REGISTRY : String = "Resource Registry"

31

PREFERENCE_REGISTRY : String = "Preference
Registry"

USER REGISTRY : String = "User Registry"

3.3.4 RegistryListener

5 This interface 345 allows an object to listen to changes made to the Registry 310.

Public Operations:

registryChange () : ApplicationRegistryEvent

This method of all registered

ApplicationRegistryListeners (e.g., RegistryListener 345) is called by the ApplicationRegistry object 330 when an ApplicationRegistryEvent is fired.

3.3.5 RegistryChangeEvent

This a generic registry change event 150 which is extended by all specific registries (such as ApplicationRegistry 330, etc.) to provide specific information about the change. It is derived from EventObject 335.

Public Operations:

getRegistryType () : java.lang.String

Returns the type of a registry that this event is associated with.

getCause () : short

Returns the cause of the RegistryChangeEvent 150.

Each derived event will define a set of causes

appropriate for the registry it represents.

Totals

15

20

25

4 Logical Packages

32

23 Classes

5

10

15

20

25

Accordingly, it can be seen that the present invention provides an application programming interface (API) for a television terminal that provides a uniform mechanism for gaining/controlling access to resources, managing multiple resources of the same type, and accessing the individual resource's management state and status as defined by the X.731 ITU-T standard. The invention is suitable for use in managing resources in a Digital Television (DTV) Receiver/Terminal.

Although the invention has been described in connection with various specific embodiments, those skilled in the art will appreciate that numerous adaptations and modifications may be made thereto without departing from the spirit and scope of the invention as set forth in the claims.

For example, while various syntax elements have been discussed herein, note that they are examples only, and any syntax may be used.

Moreover, the invention is suitable for use with virtually any type of network, including cable or satellite television broadband communication networks, local area networks (LANs), metropolitan area networks (MANs), wide area networks (WANs), internets, intranets, and the Internet, or combinations thereof.

Additionally, known computer hardware, firmware and/or software techniques may be used to implement the invention.

What is claimed is:

A television set-top terminal, comprising:
 a computer readable medium having computer program
 code means; and

means for executing said computer program code means to implement an Application Programming Interface (API) for accessing and managing multiple resources at the terminal, wherein:

the API provides a resource package for registering the available resources at the terminal, a management package for managing states of the resources, and a registry package for storing objects that represent the resources.

- 2. The terminal of claim 1, wherein: the management package manages the states of the resources according to an ITU-T X.731 standard for state management.
- 3. The terminal of claim 1, wherein the available resources include at least one of: a tuner, a modem, a database, a plug-in module, a cable, a software module, a network interface card, and a conditional access module.
- 4. The terminal of claim 1, wherein:
 the API provides a resource registry for
 maintaining a record of resource managers that provide
 access to individual resources.

- 5. The terminal of claim 1, wherein: the API is independent of an operating system and hardware of the terminal.
- 6. The terminal of claim 1, wherein: the API groups resources of the same type, and manages the grouped resources as a group.
- 7. The terminal of claim 1, wherein:
 the API monitors behavior of the resources, and
 attaches corresponding management information to the
 resources.
- 8. The terminal of claim 1, wherein: said API enables the resources to advertise their respective states to at least one application at the terminal.
- 9. The terminal of claim 8, wherein: said API enables the application to access the advertised states of the advertising resources.
- 10. The terminal of claim 1, wherein: said API enables administrative locking and unlocking of the resources.
- 11. The terminal of claim 1, wherein:
 said API enables the resources to advertise
 respective alarm statuses thereof to at least one
 application at the terminal.

35

- 12. The terminal of claim 1, wherein: said API enables the resources to advertise respective availability statuses thereof to at least one application at the terminal.
- 13. The terminal of claim 1, wherein: said API enables the resources to advertise respective procedural statuses thereof to at least one application at the terminal.
- 14. The terminal of claim 1, wherein: said API enables the resources to advertise respective operational states thereof to at least one application at the terminal.
- 15. The terminal of claim 1, wherein: said API enables the resources to advertise respective administrative states thereof to at least one application at the terminal.
- 16. The terminal of claim 1, wherein: said API enables the resources to advertise respective usage states thereof to at least one application at the terminal.
- 17. A method for implementing a software architecture for a television set-top terminal, comprising the steps of:

providing a computer readable medium having computer program code means; and

executing said computer program code means to

36

implement an Application Programming Interface (API) for accessing and managing multiple resources at the terminal; wherein:

the API provides a resource package for registering the available resources at the terminal, a management package for managing states of the resources, and a registry package for storing objects that represent the resources.









FIG.1














FIG.5



1

Intern nai Application No PCT/US 99/23358

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 H04N5/00 G06F9/46					
According to	International Patent Classification (IPC) or to both national classification	ation and IPC			
	SEARCHED currentation system followed by classification system followed by classification	on symbols)			
IPC 7					
Documentat	ion searched other than minimum documentation to the extent that s	uch documents are included in the fields se	arched		
	ata base consulted during the international search (name of data ba	so and where practical search terms used			
Electronic d	ata base consulted during the international search (name of data bu	se and, Titlere practical, search terms asser			
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT				
Category ⁵	Citation of document, with indication, where appropriate, of the rel	evant passages	Relevant to claim No.		
Α	EP 0 817 041 A (SUN MICROSYSTEMS 7 January 1998 (1998-01-07)	INC)	1,4, 7-10,12, 16,17		
	column 1, line 11 - line 16 column 2, line 54 -column 3, line column 4, line 21 - line 28	e 49	10,17		
A	EP 0 813 147 A (LSI LOGIC CORP) 17 December 1997 (1997-12-17) column 10, line 39 - line 48 column 11, line 21 - line 34		1,5,6,17		
		-/	·		
X Fun	ther documents are listed in the continuation of box C.	X Patent family members are listed	in annex.		
° Special c	ategories of cited documents :	"T" later document published after the inte	mational filing date		
"A" docum	nent defining the general state of the art which is not	or priority date and not in conflict with cited to understand the principle or th	the application but		
"E" earlier	considered to be of particular relevance invention "E" earlier document but published on or after the international filing date "X" document of particular relevance; the claimed invention cannot be considered to				
"L" docum	filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another "Y" document of particular relevance; the claimed invention				
citatio	on or other special reason (as specified) nent referring to an oral disclosure, use, exhibition or	cannot be considered to involve an in document is combined with one or me	ventive step when the ore other such docu-		
other	means nent published prior to the international filing date but	ments, such combination being obvio in the art.	·		
later	than the priority date claimed	"&" document member of the same patent Date of mailing of the international se			
,	e actual completion of the international search				
	14 January 2000	20/01/2000			
Name and	mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2	Authorized officer			
	NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fav. (-31-70) 340-3016	Sindic, G			



Intern. .al Application No PCT/US 99/23358

C.(Continuati	ion) DOCUMENTS CONSIDERED TO BE RELEVANT	
Category (Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EVAIN J -P: "THE MULTIMEDIA HOME PLATFORM" EBU REVIEW- TECHNICAL, BE, EUROPEAN BROADCASTING UNION. BRUSSELS, no. 275, 21 March 1998 (1998-03-21), page 4-10 XP000767493 ISSN: 0251-0936 figure 3 page 6, left-hand column -middle column page 7, right-hand column, paragraph 3	1,3,5,17
A	page 7, right-hand column, paragraph 3 HARTWIG S: "SOFTWAREARCHITEKTUREN FUER INTERAKTIVE DIGITALE DECODER" FERNSEH UND KINOTECHNIK, DE, VDE VERLAG GMBH. BERLIN, vol. 50, no. 3, 1 March 1996 (1996-03-01), page 92-94,96-98, XP000581418 ISSN: 0015-0142 page 96, left-hand column, paragraph 2 -right-hand column, paragraph 2 figure 1	1,3,17



Information on patent family members

Intern. .al Application No PCT/US 99/23358

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0817041	Α	07-01-1998	US JP	5826082 A 10063519 A	20-10-1998 06-03-1998
EP 0813147	A	17-12-1997	US JP	5946487 A 10069394 A	31-08-1999 10-03-1998



- 12. The terminal of claim 1, wherein:
 said API enables the resources to advertise
 respective availability statuses thereof to at least
 one application at the terminal.
- 13. The terminal of claim 1, wherein:
 said API enables the resources to advertise
 respective procedural statuses thereof to at least one
 application at the terminal.
- 14. The terminal of claim 1, wherein:
 said API enables the resources to advertise
 respective operational states thereof to at least one
 application at the terminal.
- 15. The terminal of claim 1, wherein:
 said API enables the resources to advertise
 respective administrative states thereof to at least
 one application at the terminal.
- 16. The terminal of claim 1, wherein: said API enables the resources to advertise respective usage states thereof to at least one application at the terminal.
- 17. The terminal of claim 1, wherein: the resources are used for downloadable applications at the terminal.
- 18. The terminal of claim 1, wherein the applications include at least one of:

video on demand (VOD), audio on demand, pay-perview, interactive shopping, electronic commerce, electronic program guides, Internet browsers, mail services (e.g., text e-mail, voice mail, audio mail, and/or video mail), telephony services, stock ticker, weather data, travel information, games, gambling, banking, shopping, and voting.

- 19. The terminal of claim 1, wherein: the applications enable at least one of Internet connectivity and Internet-based telephony.
- 20. A method for implementing a software architecture for a television set-top terminal, comprising the steps of:

providing a computer readable medium having computer program code means; and

executing said computer program code means to implement an Application Programming Interface (API) for accessing and managing multiple resources at the terminal; wherein:

the API provides a resource package for registering the available resources at the terminal, a management package for managing states of the resources, and a registry package for storing objects that represent the resources.

MiH



PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference		f Transmittal of International Search Report				
GIC-561 PCT ACTION (Form PCT/ISA/220) as well as, where applicable, item 5 below.						
International application No.	International filing date (day/month/year)	(Earliest) Priority Date (day/month/year)				
PCT/US 99/23358	07/10/1999	12/11/1998				
Applicant						
GENERAL INSTRUMENT CORPOR	ATION et al					
develope 1 to 1 t	TION et al.					
This International Search Report has been according to Article 18. A copy is being tra	n prepared by this International Searching Auth Insmitted to the International Bureau.	nority and is transmitted to the applicant				
	_					
This International Search Report consists It is also accompanied by	of a total of sheets. a copy of each prior art document cited in this	report.				
Basis of the report						
a. With regard to the language, the	international search was carried out on the bas ess otherwise indicated under this item.	sis of the international application in the				
the international search w Authority (Rule 23.1(b)).	as carried out on the basis of a translation of th	ne international application furnished to this				
b. With regard to any nucleotide and was carried out on the basis of the	d/or amino acid sequence disclosed in the inference listing:	ternational application, the international search				
. —	nal application in written form.					
filed together with the inte	rnational application in computer readable form	1.				
furnished subsequently to	this Authority in written form.					
	this Authority in computer readble form.					
international application as						
the statement that the info furnished	rmation recorded in computer readable form is	identical to the written sequence listing has been				
2. Certain claims were four	nd unsearchable (See Box I).					
3. Unity of invention is lacking (see Box II).						
4. With regard to the title,						
X the text is approved as submitted by the applicant.						
the text has been established by this Authority to read as follows:						
5. With regard to the abstract,						
the text is approved as submitted by the applicant. the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.						
6. The figure of the drawings to be published with the abstract is Figure No.						
X as suggested by the applic		None of the figures.				
because the applicant faile	ed to suggest a figure.					
because this figure better	characterizes the invention.					

INTERNATIONAL SEARCH REPORT

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 H04N5/00 G06F9/46

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 $\begin{array}{ccc} \text{Minimum documentation searched} & \text{(classification system followed by classification symbols)} \\ IPC & 7 & H04N & G06F \end{array}$

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUM	ENTS CONSIDERED TO BE RELEVANT	
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 817 041 A (SUN MICROSYSTEMS INC) 7 January 1998 (1998-01-07) column 1, line 11 - line 16 column 2, line 54 -column 3, line 49 column 4, line 21 - line 28	1,4, 7-10,12, 16,17
Α	EP 0 813 147 A (LSI LOGIC CORP) 17 December 1997 (1997-12-17) column 10, line 39 - line 48 column 11, line 21 - line 34	1,5,6,17

X Further documents are listed in the continuation of box C.	X Patent family members are listed in annex.
 Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filling date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filling date but later than the priority date claimed 	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family
Date of the actual completion of the international search 14 January 2000	Date of mailing of the international search report $20/01/2000$
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer Sindic, G

INTERNATIONAL SEARCH REPORT

PCT/US 99/23358

		PC1/US 99/23358
	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EVAIN J -P: "THE MULTIMEDIA HOME PLATFORM" EBU REVIEW- TECHNICAL, BE, EUROPEAN BROADCASTING UNION. BRUSSELS, no. 275, 21 March 1998 (1998-03-21), page 4-10 XP000767493 ISSN: 0251-0936 figure 3 page 6, left-hand column -middle column page 7, right-hand column, paragraph 3	1,3,5,17
4	HARTWIG S: "SOFTWAREARCHITEKTUREN FUER INTERAKTIVE DIGITALE DECODER" FERNSEH UND KINOTECHNIK, DE, VDE VERLAG GMBH. BERLIN, vol. 50, no. 3, 1 March 1996 (1996-03-01), page 92-94,96-98, XP000581418 ISSN: 0015-0142 page 96, left-hand column, paragraph 2 -right-hand column, paragraph 2 figure 1	1,3,17

INTERNATIONAL SEARCH REPORT

ation on patent family members

PCT/US 99/23358

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0817041 A	07-01-1998	US 5826082 A JP 10063519 A	20-10-1998 06-03-1998
EP 0813147 A	17-12-1997	US 5946487 A JP 10069394 A	31-08-1999 10-03-1998